








	Brands	INFOBIT	Biamp	Kramer	ScreenBeam	Mersive	Barco	CRESTRON
Cat.	Items	iShare X400	Modena Hub+	VIA connect plus	1100 Plus	Solstice gen3 pod	ClickShare CX-50	AM-3200
Pictures								
Interface	HDMI in	-	-	1	1	1	1	1
	HDMI out	1	1	1	1	2	1	1
	Max output resolution	4K/60	1080p/30	1080p/60	4K/30	4K/30	4K/30	4K/60
	USB-A 2.0	1	-	-	2	-	3	1
	USB-A 3.0	3	1	4	1	2	-	2
	USB-C	2	-	-	-	1	1	-
	LAN (100 M)	1	-	-	-	-	-	-
	LAN (1000 M)	1	1	1	1	1	1	2
	PoE	√	-	-	-	√	-	√
	Audio out	√	-	√	√	√	√	√
	RS232	√	-	-	-	-	-	√
Antenna	3	2	-	-	-	-	-	
Wireless casting	Airplay	√	-	√	√	√	√	-
	Miracast	√	-	√	√	√	√	√
	Chromecast	√	-	-	√	-	√	-
	App for different OS	√	√	√	√	√	√	√
	Web casting	-	√	√	-	√	-	√
	USB disk	√	-	-	-	-	-	-
	HDMI Dongle	√	-	-	-	-	-	-
	Type-C dongle	√	-	-	-	-	√	-
video frame rate	60fps	30fps	60fps	30fps	30fps	30fps	30fps	
Collaboration	Wireless touch back	√	√	√	√	√	√	√
	Wireless conferencing	√	√	√	√	√	√	√
	Whiteboard & Annotation	√	-	√	-	√	-	-
	Split-screen	4	6	4	4	unlimited	2	9
Control	OSD control	√	-	-	-	-	-	-
	Moderator mode	√	-	√	-	√	-	-
	3rd party control	√	-	√	-	√	√	√
Security	PIN code	-	√	√	√	√	√	√
	Dynamic wifi password	√	-	-	-	-	-	-
	Dual network	√	√	√	√	√	√	√
	Data encryption	AES & RSA	WPA2-PSK	1024-bit encryption	WPA2-PSK (AES) PEAP-MSCHAP V2 EAP-TLS	RSA/SHA cipher with a 2048-bit private key	WPA2-PSK	AES
Management platform	Central management	√	√	√	√	√	√	